



Flexsteel® Hardwall

APPLICATION:

Flexsteel® Hardwall is for dispensing pump applications that require a hardwall construction for full flow and no internal spring guards. The wire-braid construction provides excellent kink resistance, low computer creep, and long service life. UL 330 and CUL approved.



CONSTRUCTION:

TUBE: Nitrile synthetic rubber (ORS)

COVER: Black, Green, Red, Blue, or Yellow Chemivic® synthetic rubber (ORS)

REINFORCEMENT: Wire Braid

TEMPERATURE: -40°F to 140°F (-40°C to 60°C)

PACKAGING: 5/8" and 3/4" Reels or coupled lengths, 10 pieces per box / 1" Reels or coupled lengths, 5 pieces per box

BRANDING: Continuous brand "Goodyear™ 559N, Made in USA. 3/4" (19 mm) UL, CUL. Listed Flexsteel Hardwall Gasoline Hose."

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 532-327 (black) / 532-331 (green) / 532-332 (red) / 532-333 (blue) / 532-335 (yellow)

ID		NOM. OD		WEIGHT	
in.	mm.	in.	mm.	lb./ft.	kg./m.
5/8	15.9	1.00	25.4	0.38	0.57
3/4	19.1	1.13	28.7	0.44	0.65
1	25.4	1.38	35.1	0.57	0.85

The GOODYEAR (and Winged Foot Design) trademark is used by Veyance Technologies, Inc. under license from The Goodyear Tire & Rubber Company.

Goodyear Engineered Products are manufactured and sourced exclusively by Veyance Technologies, Inc. or its affiliates.

©2008 Veyance Technologies, Inc. All Rights Reserved.